UKS8202

2-Port USB KVM Switch
SOHO Plastic Case

- USB 1.1 Specification compliant

- Supports Microsoft Intellimouse , MicroSoft Intellimouse Explorer, Logitech Net Mouse, and the other Microsoft compatible mouse

- Supports hot plug function for adding or removing PCs without powering down the KVM switch or PCs

- Works with Win98 /98SE /2000 /ME /XP, /NT, Netware, SCO Unix, HP UNIX, Linux, Sun Solaris, Apple Mac OS

- Very high video quality - up to 1920x1440

- High bandwidth: 200MHz

- No software required - easy computer selection via push buttons or hot keys

- Auto scan mode for monitoring computers

- Keyboard status restored when switching computers

- LED Display for easy status monitoring for active computer

- Buzzer sound for switching port confirmation

- Works without external power adapter by   USB bus power mode

- Uses inexpensive and commonly available cables

- Compact size design, easy portable

OVERVIEW

The UKS8202 KVM Switch is an electronic switching device for controlling two computers from one PS/2 Keyboard, one PS/2 Mouse and one VGA Monitor. The KVM switch has complete keyboard and mouse emulation for simultaneous boot-up process. To switch between computers can be accomplished in two ways: through keyboard "Hot Key" commands or by using the convenient "Select" push button control.

The USB KVM switch can be used with USB type keyboard and USB type mouse as console devices. It also supports extra two comprehensive USB type A ports (if you use PS/2 console) for users to share more USB peripherals. The most significant feature is that the USB KVM Switch is compatible to AT, PS/2 style computers, SUN Microsystems computers, G3/G4 MACs or iMACs with USB port. The USB KVM switch is a multi-platform device.

KVM switch provides the best convenience for users who have multiple desktop computers and/or notebooks; or power users who need control multiple servers from one console. It saves your equipment cost, time, space, power, and provides the best convenience of operation.

SPECIFICATIONS

System Specifications	
PC Port	2 USB Type B ports
Console Port	2 USB type A ports 2 PS/2 ports
Maximum PC Connections	2
LED Indicators	2
PC Port Connector	USB Type B receptacle VGA HDB 15pin Female
Console Port Connector	USB Type A receptacle PS/2 Keyboard Mini Din 6 pin Female PS/2 Mouse Mini Din 6 pin Female VGA HDB 15 pin Female
PC Selection	Hot Key or Push Button
On Screen Display Control	No
Scan Intervals	5 ~ 100 sec. (Default 5 Sec when power on)
Keyboard Conversion	PS/2 to USB
Mouse Conversion	PS/2 to USB
VGA Resolution	1920 x 1440
Bandwidth	200MHz
Daisy Chain and Levels	No
Power Type	Bus Power, no need for power adapter
Weight	160g
Dimension	120(L) x 81(W) x 28(H) mm, SOHO Plastic Case
Emission	FCC Class B, CE
Environment	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	0% to 90% Non-Condensing

ORDERING INFORMATIONS

Model	Description
UKS8202	2-Port USB KVM Switch, SOHO Plastic Case