



## UPS1211-BU

### Mini-Size USB Print Server Mini-Size USB Port for Easy Printer Sharing

#### FEATURES

- 1xUSB 1.1-compliant port, supporting 1.5Mbps (low speed) and 12Mbps (full speed) data transmission rate
- The USB port automatically detects the maker and model of the USB printer
- Compliant with IEEE 802.3/803.2u standard Fast Ethernet network standards
- RJ-45 (UTP) connector port, 10/100Mbps auto-sensing
- Supports Network Operating System Windows 95/98/98SE/Me, Windows NT 4.0/2000/XP, Mac OS 8.1 or higher, UNIX/Linux, NetWare (Bindery/NDS)
- Supports Network Protocol TCP/IP, IPX, NetBEUI, AppleTalk, LPR
- Supports Internet Printing Protocol (IPP)
- Windows Print Monitor Technology
- Supports DHCP (client)
- Management Web Interface, Windows-based Setup Program, Telnet
- Software Upgradeable via TFTP or Windows-based Setup Program
- Supports SNMP protocol and HP Web JetAdmin
- Compact size design with external power adapter

#### OVERVIEW

The external print servers enhance company capability by letting you place your printers, or equality printers at convenient locations directly on the Ethernet network, and by increasing network printer performance and management.

The print servers support the Simple Network Management Protocol (SNMP), which remote printer management and a warning. A standard SNMP agent is permanent on these print servers. Any standard SNMP-based application can be used to access and manage these print servers.

The print servers provide an embedded web server that can be accessed via a web browser. We also subsidiary Windows-based PSAdmin utility which help administrator to setup print server environment, for example, Netware, Windows 95/98/Me, Windows NT/2000/XP, Mac or Unix system.

**SPECIFICATIONS**

<b>System Specifications</b>	
Standard	IEEE802.3 for 10BASE-T IEEE802.3u for 100BASE-TX USB 1.1 standards
Network Interface	Single RJ-45 connector for both 10Base-T and 100Base-TX
NWay Protocol Support	Network speed: 10 / 100Mbps Duplex mode: Full and Half
Cable Connections	RJ-45 (10BASE-T): UTP Category 3, 4, 5 RJ-45 (100Base-TX): UTP Category 5
Printer Interface	One standard type A USB port
Hardware Architecture	CPU: Embedded high-performance RISC-cored SoC processor Flash: 1Mbytes System Memory: 2Mbytes SDRAM USB Port USB 1.1 (full speed) standard compliant host controller LAN Port: 10/100Mbps, auto-sensing Reset Button: Yes (Reset / Load Factory Defaults)
LED indicators	LED light for status and error indications
Power Supply	3.3VDC 2A Power Supply
Dimension	55.5 (L) x 52 (W) x 22 (H) mm
Emission	CE / FCC Class A
<b>Environment</b>	
Operating Temperature	0°C to 55°C (32°F to 131°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Operating Humidity	10% to 95% Non-Condensing
Storage Humidity	0% to 95% Non-Condensing

**ORDERING INFORMATIONS**

<b>Model</b>	<b>Description</b>
UPS1211-BU	10/100Mbps Print Server with USB1.1 Printer Port

*EUSSO Technologies, Inc. is a dedicated data communication and networking company. With professional experiences in design, production, marketing and service support, we deliver the full range networking products including Gigabit Ethernet, Fiber Optic, Wireless LAN, Switches, Hubs, LAN cards, PCMCIA adapters, Converter, Transceivers. As well as Internet Telephony Gateway, Print Servers, Internet Sharing Servers and many others.*

UDS1211-BU v1.0

EUSSO Technologies, Inc.

Tel: +886-2-8221-4616

Email: sales@eusso.com

6F, No.389, Sec.2, Chung Shan Road, Chung Ho City, Taipei 235 Taiwan, R.O.C.

Fax: +886-2-8221-4607

<http://www.eusso.com>