

## USH5024-XRA

### 24-Port 10/100Mbps Nway Switch 24-Port 10/100Mbps Rackmount Nway Switch



#### FEATURES

- Complies with IEEE802.3, IEEE802.3u, IEEE802.3x standard
- 24 \* RJ-45 ports for 10Mbps and 100Mbps connectivity
- Supports Nway protocol for speed (10/100Mbps) and duplex mode (Half/Full) detection
- Every switching port is automatically cross-over detection (MDI/MDI-X auto-detected)
- Wire-speed packet filtering and forwarding rate
- Store-and-forward architecture filters fragment & CRC error packets
- Supports 8K MAC address entries in whole system
- 320K Bytes buffer memory
- Supports extensive LED indicators for network diagnostics
- 19-inch standard rack-mountable design
- Internal universal switching power supply

#### OVERVIEW

The 24-Port 10/100M Nway Switch device is a powerful, high-performance Fast Ethernet switch, with all 24 ports capable of 10 or 100Mbps auto-negotiation operation (Nway), which means the switch could automatically negotiate with the connected partners on the network speed and duplex mode. All ports support auto MDI/MDI-X function, connecting switch to switch is more convenient with non-crossover cable.

It is ideal for micro-segmenting large networks into smaller, connected subnets for improved performance, enabling the bandwidth demanding multimedia and imaging applications. Moreover, the 10/100Mbps auto-sensing ability provides an easy way to migrate 10Mbps to 100Mbps networks with no pain. Compared to the shared 10Mbps or 100Mbps networks, the switch delivers a dedicated 10/100Mbps connection to every attached client with no bandwidth congestion issue.

Store-and-forward switching mode promises the low latency plus eliminates all the network errors, including runt and CRC error packets. To work under full-duplex mode, transmission and reception of the frames can occur simultaneously without causing collisions as well as double the network bandwidth.

The switch is plug and play without any software to configure and also fully compliant with all kinds of network protocols. Moreover, the rich diagnostic LED on the front panel can provide the operating status of individual port and whole system.

**SPECIFICATIONS**

System Specifications	
Standard	IEEE802.3 for 10BASE-T IEEE802.3u for 100BASE-TX IEEE802.3x Full-Duplex and Flow Control
Interface	24 * 10/100Mbps RJ-45 Nway ports
NWay Protocol Support	Network speed: 10 / 100Mbps Duplex mode: Full and Half
Auto MDI/MDI-X Support	All 24 ports with auto MDI/MDI-X function
MAC Address Table	8K entries
System Memory	320K Bytes for the whole system
Network Data Rate	10Mbps for 10Base-T 100Mbps for 100Base-TX
Filtering/Forwarding Rate	10Mbps: 14,880pps/14,880pps 100Mbps: 148,800pps/148,800pps
Cable Connections	RJ-45 (10BASE-T): UTP Category 3, 4, 5 RJ-45 (100Base-TX): UTP Category 5
LED indicators	System: Power Port: 100M, Link/Activity
Power Supply	100~240VAC, 50/60Hz Internal Switching Power Supply
Dimension	440 x 192 x 45 mm
Emission	FCC Class A, CE
Environment	
Operating Temperature	0°C to 55°C (32°F to 131°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Operating Humidity	10% to 95% Non-Condensing
Storage Humidity	0% to 95% Non-Condensing

**ORDERING INFORMATIONS**

Model	Description
USH5024-XRA	24-Port 10/100Mbps Nway Switch

*EUSSO Technologies, Inc. is a dedicated data communication and networking company. With professional experiences in design, production, marketing and service support, we deliver the full range networking products including Gigabit Ethernet, Fiber Optic, Wireless LAN, Switches, Hubs, LAN cards, PCMCIA adapters, Converter, Transceivers. As well as Internet Telephony Gateway, Print Servers, Internet Sharing Servers and many others.*

UDS5024-XRA v1.0

EUSSO Technologies, Inc.

Tel: +886-2-8221-4616

Email: sales@eusso.com

6F, No.389, Sec.2, Chung Shan Road, Chung Ho City, Taipei 235 Taiwan, R.O.C.

Fax: +886-2-8221-4607

<http://www.eusso.com>