



UGL2454-01K

54Mbps Wireless-G 32-bit PC Card

Linking Your Notebook with Express Wireless Turbo Mode



FEATURES

- Wi-Fi compliant with IEEE 802.11g and 802.11b
- Complies with 32-bit Cardbus Type II Interface
- Supports turbo model up to 72Mbps high speed
- Supports 64/128-bit WEP wireless data encryption
- Supports advance network security of 802.1X/WPA, WPA-PSK, TKIP/AES
- Quick setup wizard and Web based user interface for easy management and configuration
- Based on 2.4GHz Direct Sequence Spread Spectrum (DSSS) Technology
- Supports Ad-Hoc (Peer to Peer) communication and Infrastructure mode with Access Point
- Supports most popular operating systems including Windows 98/Me/2000/XP/Server 2003/ Vista
- Supports Power Save mode
- Build-in diversity antenna for compact design
- Range Coverage: Indoor 35 ~ 100 meters
Outdoor: 100 ~ 300 meters

Package Contents

- One Wireless-G 32-bit PC Card
- One Quick Installation Guide
- One Setup Utility CD-ROM

OVERVIEW

The 54Mbps Wireless-G Cardbus Adapter is an advanced IEEE 802.11g/b compatible, high performance, wireless card that supports data transfer speeds of up to 54 Mbps or up to 72Mbps with turbo mode in 802.11g.

There is also integrated with a built-in infrastructure mode. Therefore, it is an ideal device for home and SOHO networking to a share high speed internet connection, files, printers, and multimedia communications with the flexibility, speed and security you need.

This Wireless-G Cardbus Adapter comes with software drivers for the most popular Microsoft Windows operating systems and can be integrated into a larger network, running Windows XP, Windows 2000, Windows ME, Windows 98SE, Windows Vista in either Ad Hoc mode (without an Access Point) or Infrastructure mode (with an Access Point).




WEP encryption and Wi-Fi Protected Access (WPA), and further enhanced with 802.1x authentication security. With drivers and utility available for most commonly used Windows OS. The 2.4GHz 802.11g/b Wireless Cardbus Adapter is a truly solid-design networking device that provides you with the ultimate freedom of wireless networking anywhere.

A setup wizard is provided as the part of the web configuration utility. You can simply follow the step-by-step process to get your wireless PC Card configuration ready to run in few easy steps by clicking on the "Wizard" button on the function menu.

SPECIFICATIONS

Wireless LAN Specifications	
Wireless Standards	IEEE 802.11g, IEEE 802.11b
Host Interface	PC Cardbus 32-bit compliant
Data Rate	802.11g: 54 / 48 / 36 / 24 / 18/ 12 / 9 / 6 Mbps auto fallback 802.11b: 11 / 5.5 / 2 / 1 Mbps auto fallback Up to 72Mbps when Turbo Mode enabled
Frequency Band	2.4GHz ISM (Industrial Scientific Medical) Band
RF Frequency	2412 ~ 2462 MHz (North America) 2412 ~ 2472 MHz (Europe) 2412 ~ 2484 MHz (Japan)
Radio Channel	1 ~ 11 channels (North America) 1 ~ 13 channels (Europe) 1 ~ 14 channels (Japan)
Range Coverage	Outdoor: 100 ~ 300 meters Indoor: 35 ~ 100 meters
Antenna type	Built-in diversity patch antenna, 2dBi gain (max.)
Roaming	Full mobility and seamless roaming from cell to cell
RF Output Power	16 – 18 dbm (typical)
Receiver Sensitivity	54Mbps OFDM, 10% PER, -68dBm 11Mbps CCK, 8% PER, -86dBm 6Mbps OFDM, 10% PER, -88dBm 1Mbps BPSK, 8% PER, -92dBm
Data Security	WPA-PSK (Wi-Fi Protected Access Pre-Shared Key) 64/128-bit WEP Encryption /Decryption
Network	Auto-switch to use 802.11g or 802.11b mode Supports Ad-Hoc, Infrastructure WLAN network Wireless roaming Data rate auto fall-back under noisy environment or longer range distance Site Survey with Profile function
Configuration & Management	Plug-and-Play setup and installation Management Utility supports Win98SE/ME/2000/XP and Vista
Media Access Control	CSMA/CA with ACK
LED Indicator	Link (Green)
Operating System	Windows 98SE / Me / 2000 / XP / Vista
Weight	46g (1.6 oz)
Dimension	118 (L) x 54 (W) x 7 (H) mm
Environment	Operating Temperature: 0°C to 40°C (32~104°F) Storage Temperature: -10°C to 70°C (32~162°F) Operating Humidity: 10% ~ 90% (Non Condensing) Storage Humidity: 10% ~ 90% (Non Condensing)
Compliant	FCC Class B (USA) CE Mark (Europe) VCCI Class B, Wi-Fi Compliant

Application Diagram



ORDERING INFORMATIONS

Model	Description
UGL2454-01K	54Mbps Wireless-G 32-bit PC Card (with Turbo Mode)

EUSSO Technologies, Inc. is a dedicated data communication and networking company. With professional experiences in design, production, marketing and service support, we deliver the full range networking products including Gigabit Ethernet, Fiber Optic, Wireless LAN, Switches, Hubs, LAN cards, PCMCIA adapters, Converter, Transceivers. As well as Internet Telephony Gateway, Print Servers, Internet Sharing Servers and many others.

2008/11/07 ver 2.0



EUSSO Technologies, Inc.

6F, No.389, Sec.2, Chung Shan Road, Chung Ho City, Taipei 235-58, Taiwan

TEL:+886 (2) 8221-4616 E-mail:sales@eusso.com

FAX:+886 (2) 8221-4607 http://www.eusso.com