

UKS8102-P2B

2-Port Mini-Size PS/2 KVM Switch

Bundle with 2 x PS/2 and Audio Cables



FEATURES

- 2-port Slim Size PS/2 KVM switch with Audio & Mic
- Audio and Microphone switching for uninterrupted multimedia experience across multi-platforms
- Simultaneous or independent PC and Audio/Mic Switching (User-programmable)
- Hot-plugging PCs for maintenance without powering down the KVM Switch or PCs
- Channel selection by both keyboard hotkeys and face-panel push buttons
- Auto scan delay time programmable
- Separate LED indicators for PC port and audio channel status monitoring
- High VGA resolution 2048 x 1536
- PS/2 interface power
- Supports Microsoft Intellimouse, Logitech Net Mouse, Microsoft mouse fully compatible mouse etc
- No software required for easy PC selection via hot keys

PACKAGE CONTENTS

- One 2-port PS/2 KVM Switch
- Two 1.2-Meter PS/2 Cables
- Two Audio and Microphone Cables
- One User's Manual

OVERVIEW

The UKS8102-P2B Slim Desktop PS/2 KVM Switch with Audio and Mic provides Audio and Microphone switching function for SOHO and office desktop multimedia application. And it allows you to access, control, boot and reboot two PS/2-enabled multimedia computers using only one keyboard, mouse, VGA monitor and optional speaker set and microphone.

The audio and microphone switching function of UKS8102-P2B allows you to leverage the multimedia systems on each of your two computers. You can monitor the audio/mic input/output of each computer without plugging on and off the audio/mic cables. And it takes only one set of speaker and microphone instead of one set for each computer.

Furthermore, it offers you user-programmable simultaneous/independent PC and Audio/mic switching function for flexible multimedia and KVM Switching operation.

The KVM switch provides the best convenience for users who have multiple desktop computers and/or notebooks; or power users who need control multiple servers from one console. It saves your equipment cost, time, space, power, and provides the best convenience of operation.

SPECIFICATIONS

System Specifications	
Functions	2-Port PS/2 KVM Switch Slim Desktop with Cable, Audio & Mic
PC Connections	2
Console Connections	1
PC Port Connectors	2 x HDB 15-pin male (integrated with PS/2 interface) 2 x USB Type Mini B (Audio & Mic)
Console Port Connectors	1 x PS/2 Keyboard 6-pin Mini Din female 1 x PS/2 Mouse 6-pin Mini Din female 1 x VGA HDB 15-pin female 1 x 3.5mm Audio in/out jack 1 x 3.5mm Mic in/out jack
PC/Audio/Mic selection	Push buttons / Hotkeys
PC port LED	2 (Green)
Keyboard/Mouse conversion	PS/2
Scan Intervals	5 – 100 Seconds
VGA Resolution	2048 x 1536
Bandwidth	400MHz
Build-in Cable Length	4 feet (1.2-meter)
Power Type	PS/2 interface power
Dimension	96 x 61 x 24 mm (L x W x H)
Safety / Emission	FCC, CE
Weight	495g
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	0% to 90% Non-Condensing

Application Diagram

PS/2 KVM Switch Application



The PS/2 KVM switch with cables is connected to PC's PS/2, VGA directly. Only one VGA Monitor, one PS/2 Keyboard, one PS/2 mouse are required to control two PCs.

PS/2 KVM Switch with Audio Application



The PS/2 KVM switch with audio function is connected to PC's PS/2, VGA, Audio port directly. Only one VGA Monitor, one PS/2 Keyboard, one PS/2 mouse and one set of speaker/microphone are required to control two PCs with audio function.

ORDERING INFORMATIONS

Model	Description
UKS8102-P2B	2-port PS/2 KVM Switch, bundle with 2 X PS/2 and Audio Cables

EUSSO Technologies, Inc. is a dedicated data communication and networking company. With professional experiences in design, production, marketing and service support, we deliver the full range networking products including Gigabit Ethernet, Fiber Optic, Wireless LAN, Switches, Hubs, LAN cards, PCMCIA adapters, Converter, Transceivers. As well as Internet Telephony Gateway, Print Servers, Internet Sharing Servers and many others.

2006/2/15 ver 1.0